



British Electric Lamps
Looking to the future

FirestayLED

- 8W COB Integrated Pro LED Downlights
- 30 / 60 / 90 minutes certified firestay
- Part B / C / E / L compliant
- Tridonic dimmable driver
- Screwless terminals on driver & fittings
- 7 year domestic guarantee³
- Twistlock Bezel accessory (Fixed Only)
- IP65 (Fixed only)
- No need for removal of driver for insulation resistance testing



Tilt Downlight

Fixed Downlight



Fine tune your LED dimming with the **BELL LED Dimmer Module**:
250W load / 20 Fittings
See page 25

Tridonic Driver
Surge protected at 3750V, suitable for insulation resistance testing without removing the driver from the circuit



Fixed Downlights						
Code	Colour	Finish	lm	cd	Beam	Hrs
08100	3000K	Round White	530	700	40°	40000
08101	3000K	Round Satin	530	700	40°	40000
08110	4000K	Round White	550	700	40°	40000
08111	4000K	Round Satin	550	700	40°	40000
Tilt Downlights						
08120	3000K	Round White	530	700	40°	40000
08121	3000K	Round Satin	530	700	40°	40000
08123	3000K	Round Matt Black	530	700	40°	40000
08125	3000K	Round Matt White	530	700	40°	40000
08124	3000K	Round Brass	530	700	40°	40000
08126	3000K	Round Ant Brass	530	700	40°	40000
08127	3000K	Round Gunmetal	530	700	40°	40000
08122	3000K	Round Chrome	530	700	40°	40000
08130	4000K	Round White	550	700	40°	40000
08131	4000K	Round Satin	550	700	40°	40000
08133	4000K	Round Matt Black	550	700	40°	40000
08135	4000K	Round Matt White	550	700	40°	40000
08134	4000K	Round Brass	550	700	40°	40000
08136	4000K	Round Ant Brass	550	700	40°	40000
08137	4000K	Round Gunmetal	550	700	40°	40000
08132	4000K	Round Chrome	550	700	40°	40000

Twistlock Bezel accessory (Fixed Only)		
Code	Style	Finish
08152	Round	Matt Black
08153	Round	Matt White
08154	Round	Brass
08155	Round	Ant. Brass
08156	Round	Gunmetal
08150	Round	Chrome
08162	Square	White
08160	Square	Satin
08165	Square	Matt Black
08164	Square	Matt White
08166	Square	Brass
08167	Square	Ant. Brass
08168	Square	Gunmetal
08161	Square	Chrome

Emergency Pack	
Code	Description
08147	Emergency Pack for Pro LED 8W Firestay

IC Cages for insulation cover	
Code	Description
08176	For Fixed Downlight
08177	For Tilt Downlight



- Use where insulation material is present for improved air flow and cooling

Spacer Plates for Large Cut-Outs	
Code	Description
08170	White Ø 180mm
08171	Satin Ø 180mm
08172	Chrome Ø 180mm



- Used to cover existing ceiling holes Ø70mm - Ø100mm only
- Fixed Downlights only




British Electric Lamps
Looking to the future

FirestayLED


Technical Specification

Data	
Construction	Aluminium
Driver	Tridonic
LED Chip	Sharp
IP Rating	IP20
Operating Temp	-5°C to +35°C
Input Voltage	220 - 240V
Power Factor	> 0.9
CRI	85 - Exceeds EU standard of Ra 80 for Colour Rendering Index
LMR	80 - Exceeds EU standard of 70 for Lumens Maintenance Ratio
ECA Compliant	Yes
L1A / L1B / L2A / L2B Compliant	Yes


Warm White




Cool White



Fixed Downlight



Tilt Downlight



Tool free installation

Press release connectors
Suits cable Ø0.7mm - Ø2.5mm,
Loop in/out terminals for speed of
Installation



¹ Exceeds EU standard of 70 for Lumens Maintenance Ratio
² Exceeds EU standard of Ra 80 for Colour Rendering Index
³ Subject to terms & conditions