



British Electric Lamps
Looking to the future

Firestay

- Fixed / Centre Tilt / Showerlight IP65 Downlights
- 30 / 60 / 90 minutes certified firestay
- Part B / C / E compliant
- MR16/GU10 lamps
- Suitable for 12V or 240V lamps
- Loop in/out terminals for speed of installation
- Die-cast aluminium body
- Twist lock lamp retaining mechanism
- Part L compliant with BELL 7W LED GU10 and 8W LED MR16
- IP65 (Showerlight only)
- L1A / L1B / L2A / L2B Compliant

One fitting to fit all standard type lamps

Simply choose a BELL lamp for the application required

(See page 83)






British Electric Lamps
Looking to the future

Firestay


Technical Specification

Fixed Downlight




Cut-Out: 70mm

Centre Tilt Downlight



Cut-Out: 80mm

Showerlight IP65



Cut-Out: 75mm

Code	V	Description	Finish	Cut Out
08590	12/240	Fixed Downlight	White	70
08591	12/240	Fixed Downlight	Matt White	70
08592	12/240	Fixed Downlight	Satin Nickel	70
08593	12/240	Fixed Downlight	Chrome	70
08594	12/240	Fixed Downlight	Satin Silver	70
08595	12/240	Fixed Downlight	Antique Brass	70
08596	12/240	Fixed Downlight	Brass	70
08583	12/240	Centre Tilt Downlight	White	80
08584	12/240	Centre Tilt Downlight	Matt White	80
08585	12/240	Centre Tilt Downlight	Satin Nickel	80
08586	12/240	Centre Tilt Downlight	Chrome	80
08587	12/240	Centre Tilt Downlight	Satin Silver	80
08588	12/240	Centre Tilt Downlight	Antique Brass	80
08589	12/240	Centre Tilt Downlight	Brass	80
08572	12/240	Showerlight IP65	White	75
08573	12/240	Showerlight IP65	Matt White	75
08574	12/240	Showerlight IP65	Satin Nickel	75
08575	12/240	Showerlight IP65	Chrome	75
08576	12/240	Showerlight IP65	Satin Silver	75
08577	12/240	Showerlight IP65	Antique Brass	75
08578	12/240	Showerlight IP65	Brass	75



¹ Exceeds EU standard of 70 for Lumens Maintenance Ratio
² Exceeds EU standard of Ra 80 for Colour Rendering Index
³ Subject to terms & conditions