



COLLINGWOOD
LIGHTING



FL10

100W colour switchable floodlight

FEATURES

Wattage	100W	UGR rating	UGR 14
Color Switchable	Yes	Input	Mains
IP Rating	IP65	Dimmable	No
Tilttable	180°	LED lifetime	25,000h
Rotatable	360°	Flicker free	Yes
Mounting position	Wall surface	Sensor	No

PHOTOMETRICS @ 25°C

Colour	Beam angle	Product code	CRI	lm	lm/W	lx at 1m
6500K*	120°	FL10BXCS	>80Ra	10970	110	4575
4000K*	120°		>80Ra	11810	118	4926
3000K*	120°		>80Ra	10250	103	4275

*CCT is selected by a switch on the rear of the product

INSTALLATION INFORMATION

Weight	2100g	Inrush current	75A 0.005ms
Construction material	Black painted cast aluminium	Bathroom Zone	-
Face temperature	60°C	Ambient temperature	40°C

WIRING INFORMATION

Cable / flying lead	1000mm Ø7mm, H05RN-F3-core
Type of wiring required	Parallel (mains) 220-240V AC 50/60Hz

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
N/A (integrated SELV driver)	220-240V	-	No	-	N/A	N/A

ACCESSORIES

Product code	Description
N/A	No accessories required

GUARANTEE / WARRANTY

3 year guarantee

FEATURES & BENEFITS


First mount, detachable circular bracket for speed of install

Total flexibility with a unique 360° rotation

Flicker free for visual comfort

High efficacy – up to 118lm/W

Black cast aluminium body for a contemporary design



Beam angle: 120° C0/C180 / 120° C90/C270

Additional diagrams available at collingwoodlighting.com

