

GREAT DEALS

SAVE £££'S

NEW PRODUCTS

FOR EVERY PRODUCT WITH AN NEXT TO IT, WE* WILL DONATE THE AMOUNT STATED NEXT TO THE PRODUCT IN GREEN [PLUS VAT] TO MACMILLAN CANCER SUPPORT** POR TERMS





390 STORES



OVER 35,000 ITEMS IN STOCK ONLINE



OVER 300 BRANDS









IN-STORE | CEF.CO.UK | TRADE CATALOGUE | APP

M18 FUEL™ BRUSHLESS TWIN PACK

2664-5272

[M18 FPD2] PERCUSSION DRILL

- Max. Torque: 135 Nm
- No load speed: 0 550 / 0 2,000 rpm
- Percussion rate: 0 32,000 bpm
- Max. Drilling capacity: [Wood]: 89 mm [Metal]: 16 mm [Masonry]: 16 mm
- Weight with battery: 2.2 kg

[M18 FID2] IMPACT DRIVER

- Max. Torque: 119 / 176 / 226 Nm
- No load speed: 0 1,900 / 0 2,800 / 0 3,600 rpm
- Impact rate: 0 1,200 / 0 3,400 / 0 4,300 ipm
- Drive size: ¼" Hex Weight with battery: 1.7 kg

PACK CONTENTS:

- 4 x Batteries: High output Li-lon 3Ah
- Multi-volt fast charger

 Packout™ carry case







1ST JUNE - 31ST AUG 2021

M18 FUEL™ PERCUSSION DRILL AND SDS+ HAMMER DRILL TWIN PACK

2664-5275

IM18 FPD21 PERCUSSION DRILL

- Max. Torque: 135 Nm
- No load speed: 0 550 / 0 2.000 rpm
- Percussion rate: 0 32,000 bpm
- Max. Drilling capacity: [Wood]: 89 mm [Metal]: 16 mm [Masonry]: 16 mm
- Weight with battery: 2.2 kg

PACK CONTENTS:

- 2 x Batteries: Li-lon 6Ah 2 x Carry case
- Multi-volt fast charger

[M18 CHX] SDS+ HAMMER DRILL

- No load speed: 0 1,400 rpm
- Impact energy: 2.5J
- Percussion rate: 0 5,100 bpm
- Max. Drilling capacity: [Wood]: 30 mm [Metal]: 13 mm [Masonry]: 26 mm

TEMPTION

• Weight with battery: 3.5 kg







M18 FUEL™ MULTITOOL

[M18 FMT-522X] 2648-4166

- No load speed: 10,000 20,000 opm
- Oscillation angle left / right: 2.1°
- 180° LED Light Weight with battery: 1.6 kg

INCLUDES:

- 2 x Batteries: 1 x Li-lon 2Ah and 1 x Li-lon 5Ah
- Multi-volt fast charger
- Carry case Wood blade
- Sanding pad

 5 x Various grit sanding paper







1 [M18 FPD2] PERCUSSION DRILL

M18 FUEL™ 6 PCE SET

Max. Torque: 135 Nm

2664-5278

- No load speed: 0 550 / 0 2,000 rpm
- Percussion rate: 0 32,000 bpm
- Max. Drilling capacity: [Wood]: 89 mm [Metal]: 16 mm [Masonry]: 16 mm
- Weight with battery: 2.2 kg

2 [M18 FID2] IMPACT DRIVER

- Max. Torque: 119 / 176 / 226 Nm
- No load speed: 0 1,900 / 0 2,800 / 0 - 3,600 rpm
- Impact rate: 0 1,200 / 0 3,400 / 0 - 4,300 ipm
- Drive size: 1/4" Hex
- Weight with battery: 1.7 kg

SET CONTENTS:

- 2 x Batteries: Li-Ion 5Ah
 Wheeled bag
- Multi-volt fast charger

3 [M18 CHX] SDS+ HAMMER DRILL

- No load speed: 0 1,400 rpm
- Impact energy: 2.5J
- Percussion rate: 0 5,100 bpm
- Max. Drilling capacity: [Wood]: 30 mm [Metal]: 13 mm [Masonry]: 26 mm
- Weight with battery: 3.5 kg

4 [M18 CAG115XPDB] ANGLE GRINDER

- Max. Disc diameter: 115 mm[Ø]
- No load speed: 0 8,500 rpm
- Spindle thread: M14
- Vibration: [Grinding]: 2.11 m/s² [Sanding]: 1.83 m/s²
- Weight with battery: 2.7 kg







5 [M18 FMT-0] MULTITOOL

10,000 - 20,000 opm

Oscillation angle left / right: 2.1°

Weight with battery: 1.6 kg

6 [M18 AL-0] LED AREA LIGHT

Two brightness levels

Built-in handle – hang

Max. Run time: 10 hrs

vertically or horizontally ■ Max. Lumen output: 1,500 lm

Weight with battery: 2.1 kg

No load speed:







MILWAUKEE KITS

How to redeem:

Buy any Milwaukee kit from our Just the Job range before 30th June

CLAIM FREE MILWAUKEE PRODUCTS WHEN YOU PURCHASE SELECTED

1ST - 30TH JUNE 2021

- Submit your proof of purchase for validation at: uk.milwaukeetool.eu/redemption
- Redeem your Milwaukee tool or product free of charge

T&Cs apply (see uk.milwaukeetool.eu/redemption for details)

390 STORES









UNIVERSAL DYNACASE BOX

2262-1057

■ Dimensions: 475 mm[L] x 358 mm[W] x 135 mm[D]











No load speed: 10,000 - 20,000 opm

Oscillation angle left / right: 1.8°

M12™ PIVOT AREA LIGHT

[M12 PAL-0] 2648-4223

Max. Run time: 24 hrs

■ 40° Rotatable head

ONLY

COFUEL

■ Max. Lumen output: 700 lm



M12™ DAB+ RADIO AND CHARGER

[M12 RCDAB+ 0] 2630-0464

■ USB and M12™ charging port

 Various hanging options

■ IP54





OO FUEL

Bluetooth

M12 FUEL™ WET / DRY VACUUM

[M12 FVCL-0] 2642-0266

■ Capacity: 6.1 Ltr



Flexible hose

 Crevice tool Wall mount

 Utility nozzle Certified HEPA filter







■ Max. Cutting capacity: 64 mm





12V XR DRILL DRIVER AND IMPACT DRIVER KIT

[DCK211D2T-GB] 2449-6570

[DCD710] COMBI DRILL

- No load speed: 0 - 400 / 0 - 1,500 rpm
- Max. Torque: 24 Nm
- Torque settings: 15
- Max. Drilling capacity: [Wood]: 20 mm [Metal]: 10 mm
- Chuck capacity: 10 mm
- Weight with battery: 1.1 kg

[DCF815] IMPACT DRIVER

- No load speed: 0 - 2,450 rpm
- Impact rate: 0 - 3,400 ipm
- Max. Torque: 107 Nm
- Max. Bolt diameter: M10
- Bit holder: 6.35 mm [1/4"]
- Weight with battery: 1.04 kg



- 2 x Batteries: XR Li-lon 2Ah
- Multi-volt XR charger
- TSTAK V Kit box

DEWALT

18V XR CORDLESS MULTITOOL

[DCS355M1] 2280-6376

- Variable speed settings
- No load speed: 0 20,000 opm
- Oscillating angle left / right: 1.6°
- LED Light illuminates dark work surfaces for accurate cutting

INCLUDES:

- 31 mm x 43 mm Fast cut wood blade
- 31 mm x 43 mm Nail embedded wood blade
- Rigid scraper blade
- Semi-circle blade
- Carbide grout removal blade
- Wood detail blade
- Sanding pad
- 25 x Assorted sandpaper sheets
- Depth control guide
- Dust extraction adpator
- Universal blade adaptor
- Battery: XR Li-ion 4Ah
- Multi-volt XR charger
- TSTAK Kit box

DEWALT

18V XR BRUSHLESS SDS+ HAMMER DRILL

[DCH133M1] 2572-8739

- No load speed: 0 1,550 rpm
- Impact energy: 2.6J
- Percussion rate: 0 5,680 bpm
- Max. Drilling capacity: [Wood]: 30 mm [Metal]: 13 mm [Masonry]: 26 mm
- Vibration impact: 14.5 m/s²
- Weight with battery: 2.9 kg

INCLUDES:

- Battery: XR Li-lon 4Ah
- Multi-volt XR charger
- TSTAK Kit box



18V XR BRUSHLESS 115 MM CIRCULAR SAW – BODY ONLY

[DCS571N] 2664-5263

- Max. Disc diameter: 115 mm[Ø]
- No load speed: 0 4,500 rpm
- Max. Cutting depth: [90°]: 38 mm [45°]: 25 mm

INCLUDES:

- 115 mm TCT 24T Blade Dust protector
- Hex key



18V / 54V XR FLEXVOLT COMBI DRILL AND SDS+ HAMMER DRILL

[DCK2033X2] 2571-1210

(DCD996) COMBI DRILL

- No load speed: 0 450 / 0 1,300 / 0 2,000 rpm
- Percussion rate: 0 8,600 / 0 25,500 / 0 38,250 bpm
- Max. Torque: 95 Nm
- Max. Drilling capacity: [Wood]: 55 mm

[Metal]: 15 mm [Masonry]: 13 mm

• Chuck capacity: 13 mm

IDCH3331 SDS+ HAMMER DRILL

- No load speed: 0 1,000 rpm
- Impact energy: 3.5J
- Percussion rate: 0 4,480 bpm
- Max. Drilling capacity: [Wood]: 30 mm [Metal]: 13 mm [Masonrv]: 30 mm
- Weight with battery: 3.7 kg

INCLUDES:

- 2 x Batteries: XR FLEXVOLT Li-lon 9Ah
- Multi-volt XR charger
- TSTAK Kit box

DEWALT



54V XR FLEXVOLT BRUSHLESS WALL CHASER

[DCG200T2] 2669-6233

- No load speed: 0 9,000 rpm
- Bore size: 22.23 mm
- Blade diameter: 125 mm[Ø]
- Blade thickness: 3 mm
- Spindle diameter: 14 mm[Ø]

390 STORES

- Cutting depth: 32 mm • Cutting width: 35 mm
- Weight with battery: 4.8 kg
- **INCLUDES:**
- 2 x Batteries: XR FLEXVOLT Li-lon 6Ah
- Multi-volt XR charger
- TSTAK Kit box









DEWALT





MULTIFUNCTION TESTER – MFT 1741

2315-1076

Enhanced non-trip loop impedance measurement technology

- Built-in confidence meter
- Variable testing of RCD types: AC, A, S, Type B [DC], plus programmable and 3 phase RCDs
- Ramp test and auto RCD test
- 2 and 3 Pole earth spike testing
- Insulation testing at 100, 250, 500V and 1 kV
- Continuity and resistance: 15 mA or 200 mA tests
- Internal memory and Bluetooth® communications
- Simple colour-coded test selection
- Adjustable buzzer threshold
- True RMS system voltage and frequency measurement
- EN 61010 CAT IV safety rating
- IP54

INCLUDES:

- Switched probe







Megger.

■ 3 Wire lead set with

- probes and croc clips
- Mains plug test lead
- Neck strap
- 6 x Batteries: NiMH Rechargeable 1.2V

FLUKE

MULTIFUNCTION TESTER – FLUKE 1662

Soft pouch

Calibration certificate

AC Battery charger

2185-2499

- Insulation resistance, continuity, loop and line resistance
- On / Off switchable auto-start for RCD and loop test
- Voltage and frequency
- Wiring polarity checker detects broken N wires
- Measure motor windings with continuity test
- Automatic RCD test sequence
- Prospective earth fault current
- Prospective short circuit current
- RCD switching time
- RCD tripping level [ramp test]
- Measures trip time and current for RCD type A and AC in one test
- IP40

INCLUDES:

- 3 Wire lead set with probes and croc clips
- Switched probe
- Zero adaptor
- Mains plug test lead
- Padded neck strap
 - Hard carry case
 - 6 x Batteries: AA / LR6 1.5V



ΕΤΗΩS **MULTIFUNCTION TESTER - ETHOS 8400** Test Instrument 2028-7258 INCLUDES: ■ Simple to operate – just select and test 3 Wire lead set with Large full colour display with probes and croc clips precise easy to read values Switched probe ■ High accuracy non-trip loop Mains plug test lead testing Calibration certificate PEFC and PSCC testing Heavy-duty carry case Auto sequence RCD testing 6 x Batteries: AA 1.5V ■ Type 'A' RCD test Auto RCD Ramp test Selective / time delay RCD tests Insulation resistance testing for 250, 500 and 1,000V 3 YEAR Phase rotation / sequence test ■ Battery saving 'Auto Sleep' mode with fast pushbutton restart Polarity check with full colour indication ■ IP54

MULTIFUNCTION TESTER – TIS MFTECO

2612-5537

- Large COG graphic LCD display [128 x 128 pixels]
- RCD Testing: 6 mA to 1A
- 2 Wire accurate and stable no trip loop test
- L-N, L-PE with PSC and PFC results on the no trip loop test displayed
- Automatic testing of all 3 insulation tests in one test
- Auto loop and RCD test on one push of the test button
- Tripping of general and selective type AC, A and S RCDs
- Insulation testing at 50, 100, 250, 500 and 1,000V
- Built in fuse characteristics
- Phase to phase loop testing
- Dual test buttons for left or right handed use
- True RMS for accurate measurements on noisy and distorted circuits
- New auto start testing mode
- Built-in pass / fail levels
- Warranty: 1 Year [extendable to 3 years]

INCLUDES:

- 3 Wire lead set with probes and croc clips Mains plug test lead
- Harness
- PR400 Remote switch
 Soft padded carry case
- Calibration certificate
 6 x Batteries: AA 1.5V







Neck strap



THERMAL IMAGING CAMERA

2606-4961

- Easy to use single button capture
- Colour palettes and blended image for analysis
- Colour screen: 56 mm TFT
- Spotmeter: Centrespot, auto hot or cold markers
- Integral memory: Store up to 6,000 images
- Temperature range: -20 to 300°C

INCLUDES:

- Charger adaptor
- USB Lead
- USB Mains charger
- 4GB Micro SD card
- SD Card adaptor
- Tripod
- Rechargeable battery: Li-lon



AUTO-RANGING DIGITAL MULTIMETER

2148-9301

- True RMS
- Diode test
- Audible continuity test
- Data hold function
- Battery and resistance test
- Voltage range: 0 - 600V AC / DC

INCLUDES:

- Red / black test leads
- Battery: PP3 9V

ΕΤΗΩ

2 YEAR

FLUKE.

Current range: 0 - 15A AC / DC

CAT II 1,000V and CAT III 600V

ONLY

DIGITAL MULTIMETER

ΕΤΗΩ

FLUKE

2148-9295

- Data hold function
- Current: 10A AC / DC CAT II 500V and CAT III 300V
- Continuity buzzer
- Backlit display
- Low battery indicator
- Voltage: 500V AC / DC



INCLUDES:

- Red / black test leads
- Battery: Button cell CR2032 3V

SAFETYPAT ELITE PAT TESTER KIT

2465-1571

- Downloads to a SD card minimum 3000 results
- Full QWERTY keyboard for fast data entry
- Automatically creates test result certificates
- Tests 110V. 230V and 415V appliances and equipment
- Battery and mains operation
- · Class I, Class II, leads, polarity 230V and 110V sub-leakage tests functionality
- Auto power Off
- No expensive software upgrades every year

KIT CONTENTS:

- Earth bond test lead
- IEC Test lead
- Plug lead probe and croc clips
- 110V 2P+E Socket to 13A plug adaptor
- 110V 2P+E Plug to IEC socket adaptor
- Mains adaptor
- 8GB SD Card
- Pass labels
- Neck strap
- Carry case
- 8 x Batteries: AA 1.5V



VOLTAGE AND CONTINUITY TESTER

1578-8287

T15

- Detects AC / DC voltage: 12 690V
- LED Indicator for AC / DC voltage detection
- Detects voltage even with discharged batteries
- Phase rotation
- Single phase voltage offers fast identification of live conductors
- IP54
- IEC EN 61243-3
- GS38 Compliant

INCLUDES:

2 x Batteries: **AAA 1.5V**



OPEN JAW DIGITAL CLAMP METER

2384-0884

- True RMS
- FieldSense contactless measurement
- Voltage: 1 1,000V AC / DC
- Current: 0.1 200A AC
- Resistance: 1 100 kΩ
- Frequency: 45 66 Hz
- Jaw opening: 17.8 mm
- Dual display
- CAT III 1,000V and

CAT IV 600V

INCLUDES:

- Test leads
- Carry case
- 2 x Batteries: AA 1.5V

ONLY

2 YEAR

MT+5

PAT TESTER KIT

2265-1657

- Class I, II and extension lead tests
- IEC Lead test
- 200 mA Earth continuity
- 500V Insulation resistance
- 110V Compatible

Battery powered

- Clear pass or fail indication

KIT CONTENTS:

- PAT Tester check box
- 110V 2P+E Socket to 13A plug adaptor
- Set of pass and fail labels
- PAT Record book
- Ethos work bag
- 6 x Batteries: AA 1.5V



VOLTAGE AND CONTINUITY TESTER

2222-1574

- Voltage range: 12 1,000V AC / DC
- LCD, LED, Audible and vibrating indications of voltage and continuity
- Removable shuttered lead set
- Indicates by LED with or without battery power
- 30 mA RCD Test with non-trip function
- Built-in backlight and torch 3 Phase rotation detection
- Built-in non-contact voltage detector

- Resistance and capacitance built-in
- IP65

2 YEAR

- BS EN 61243-3
- GS38 Compliant

INCLUDES:

- Padded case
- 2 x Batteries: AA 1.5V





11













()T15



CIRCUIT BREAKER FINDER AND SOCKET TESTER

1735-9297

- Advanced micro processor locates the fuse / breakers accurately using the latest 2nd pass technology
- Transmitter also acts as a socket tester with buzzer
- Non-contact voltage detection
- Fully automatic operation
- Two part kit: Transmitter and receiver
- Buzzer and LED indication



⊕715 SOCKET, LOOP AND **RCD TESTER**

1976-3731

12

- Tests 13A sockets
- Simply plug in for visual and audible indication
- 30 mA RCD Test
- Earth loop impedance check
- Built-in self check



EARTH LEAKAGE CLAMP METER

1765-2376

- Compact size
- AC Current ranges: 2 mA, 20 mA and 60A
- Earth leakage: 0.001 mA
- Conductors up to 31 mm[Ø]
- Data hold
- Low battery warning
- LCD Screen
- Conforms to the latest 18th edition regulation 531.3.2
- CAT III 600V

INCLUDES:

- Wrist strap 2 x Batteries: AAA 1.5V
- Carry case



()T15

LASER DISTANCE METER

390 STORES **OVER 35,000**







2 YEAR

Megger.

8

1 YEAR

Visibility range: 40 m

Accuracy: ± 2 mm

2369-4037

- Area / volume calculations
- Addition / Subtraction
- Pythagorean and tracking measurements



CAT III 600V

GS38 compliant

INCLUDES:

1354-2055

2 x Batteries: AAA 1.5V

For use with most

SET CONTENTS:

• 3 x Croc clips

■ 3 x Probes

multifunction testers

Unfused test leads: 1.4 m

• 3 x Test leads with 4 mm plugs:

• 2 x Extended probes: Red and blue

Red, blue and green

3 WIRE TEST LEAD SET



voltages: 50 - 690V Non-contact voltage

- Auto power On / Off
- protective surround



Megger. **EV CHARGE POINT ADAPTOR**

2633-0122

- Full range of safety and functional tests achievable through connection to a multifunction tester
- Simulates vehicle connection and tests all Mode 3 EV stations
- Check for hazardous touch voltage with PE pre-test
- Error simulation states: E and PE
- Control pilot simulation states: A. B. C and D
- Proximity pilot simulation states: Open circuit, 13A, 20A, 32A and 63A
- IP54

INCLUDES:

 Type 1 and Type 2 connectors for testing tethered cables and socket outlets

LOCKOUT KIT

ONLY

MCG

CONTRACTOR LOCKOUT KIT

2483-8717

 Ideal for a contractor working on commercial, industrial or domestic installations and routine maintenance schedules

KIT CONTENTS:

- Red safety padlock [1 key]
- Universal MCB lockout
- Plunge MCB lockout [pin-in]
- Plunge MCB lockout [pin-out]
- Grip tight MCB lockout [sideways]
- Grip tight MCB lockout [over toggle]
- Steel lockout hasp
- 5 x Reusable lockout tags
- 5 x Cable ties
- Non-permanent pen
- Zipped carry bag





STAND-UP ZIPPER BAGS

WIN £10,000 WORTH OF KLEIN & SUPER ROD TOOLS

Purchase any Klein or Super Rod product for your chance to win!

SUPERROD PROFESSIONAL KIT

2651-5276

CABLE ROD DELUXE SET INCLUDES:

- 2 x 6 mm Black Adoxim 5® 1 m rods
- 6 x 5 mm Red Adoxim 5® 1 m rods
- 2 x 4 mm Yellow Adoxim 5® 1 m rods
- Flexi lead
- Domed bullet
- Flat bullet
 - Gender changer
 - Super magnet
 - Super beam
 - Tuff hook
 - Mini eye and ring
 - Tough carry tube

POLYMER ROD SET INCLUDES:

- 5 mm x 330 mm Round black rod
- 5 mm x 330 mm Round red rod
- 5 mm x 330 mm Flat red rod
- 5 mm x 330 mm Round glow rod
- Domed bullet
- Mini eve
- Glow claw Domed eve





Mini hook

Glo alider

Super Rod

carry case



FERRET™ WI-FI INSPECTION CAMERA KIT

2604-7951

- Ideal for visual inspections, installations and troubleshooting
- View photos or stream 720p video directly to your smart device
- Retrieve and recover objects using the hook and magnet attachments
- Adjustable bright white LED torch
 IP67
- Rechargeable Operating time:
- Up to 100 mins • Quickly charges:
- 70 mins ■ Wi-Fi range: 12 m

KIT CONTENTS:

- Wi-Fi Inspection camera
- USB-C Charge cable
- Thread adaptors
- Flexible gooseneck
- 1.4 m Telescopic ferret stick
- Short rod

11 PCE TOOL KIT

2651-5279

- Premium quality tool kit for the professional electrician
- Tradesman Pro[™] Organiser backpack with 39 pockets for ample storage

KIT CONTENTS:

- Tradesman Pro[™] tool bag backpack
- VDE Slotted screwdrivers: SL2.5, SL4 and SL5.5 mm
- VDE Pozi screwdrivers: PZ1 and PZ2
- VDE Insulated combination pliers - 225 mm
- VDE Diagonal cutters 160 mm



- 3.6 m Cable tongue

ONLY Hook Magnet Padded EVA case

ONLY 7.5 m Double-hook magnetic tape measure Rare earth magnet aluminium torpedo level - 229 mm

FOR MORE INFO ASK IN-STORE OR GO TO CEF.CO.UK/BUYTOWIN DON'T MISS OUT!



1906-0267

- Quick and easy stripping 0.5 - 4 mm² solid core and 0.34 - 2.5 mm² stranded
- Adjustable stopper to control the length of the core strip

1906-0273

Toothed

• Convenient wire cutter in handle

Crimping die behind hinge

for superior leverage

when crimping

greater control Overall length: 225 mm

Integral thumb guard

VDE Safety certified

pipe grip for

■ 1,000V Rated

VDE ELECTRICIAN'S

COMBINATION PLIERS



ONLY

DIMENSIONS:

■ Pack of 2

- Orange: 165 mm[H] x 216 mm[W] x 70 mm[D]
- Grev: 191 mm[H] x 229 mm[W] x 70 mm[D]



COMPACT MODULAR **RATCHET CRIMPING AND** STRIPPING TOOL

1906-0426

- Multifunction tool cuts. strips and crimps data and voice cables
- Crimps six and eight position modular connectors



VDE INSULATED SCREWDRIVERS

• Ergonomic handle provides greater torque and comfort

- 1.000V Rated
- VDE Safety certified
- IEC 60900 and ASTM F1505

[2173-1965] SET CONTENTS:

- Pozi: P71 and P72
- Slotted: SL2.5. SL4 and SL5.5 mm
- Tough storage case

CODE	TIP TYPE	SIZE	BLADE LENGTH	PRICE
2173-2286	Phillips	PH1	80 mm	£8.75
2173-2280	Pozi	PZ1	80 mm	£8.95
2173-2283	Pozi	PZ2	100 mm	£10.50
2173-2277	Slotted	SL6.5 mm	150 mm	£10.50



DESCRIPTION 2173-1965 5 PCE Screwdriver Set



















5 PCE VDE TRITON

SCREWDRIVER SET

XLS INSULATED

7 PCE VDE ERGO™ **SCREWDRIVER SET**

0103-1074

- Three component handle for maximum user comfort and leverage
- Colour-coded handle with tip type symbol for ease of selection
- Anti-roll design prevents tool loss
- 1,000V Rated
- VDE Safety certified
- IEC 60900

SET CONTENTS:

- Pozi: PZO, PZ2 and PZ3
- Slotted: SL2.5, SL3, SL4



BAHCO

SET CONTENTS:

1035-8038

Anti-roll design

Toughened alloy

steel blade for

1,000V Rated

prevents tool loss

excellent durability

VDE Safety certified

- Pozi: PZ1 and PZ2
- Slotted: SL2.5. SL4 and SL5.5 mm



and SL5.5 mm

180 MM ERGO™ VDE SIDE CUTTER

0044-5564

- Induction hardened cutting edges
- Black finish, anti-corrosion treated
- Cuts hard wire
- Integral thumb guard
- 1,000V Rated
- VDE Safety certified



PROFESSIONAL HACKSAW



2227-5103

Comfortable soft-grip handle

• 100 kg Blade tension ensures easier cutting

- Blade length: 300 mm
- Teeth per inch: 24
- Blade positions: 0 and 55°

INCLUDES:

1 x Sandflex blade as standard





ARMOURSLICE SWA CABLE STRIPPER

1870-5430

- Robust metal alloy body for exceptional strength and durability
- For stripping cable 12 36 mm[Ø]
- Fast, clean, safe stripping of SWA cables up to 50% quicker than conventional stripping methods
- Integrated spare blade holder for guick blade changes







- For boot lace ferrules
- Safe and secure crimping
- Auto-stop ratchet releases when correct pressure is applied
- Terminal size: $0.14 - 2.5 \, \text{mm}^2$



PVC PIPE AND CONDUIT CUTTER

0018-6619

- Suitable for efficient cutting of PVC conduits, blue water mains, rubber hose and pneumatic pipe
- Strong, lightweight fibreglass-reinforced polycarbonate body
- Razor sharp stainless steel blade
- Jaw capacity: 25 mm[Ø]





RETRACTABLE BLADE CK **SOFT-GRIP TRIMMING** KNIFE 0620-9530 Magnetic blade retainer and Heavy-duty, die-cast aluminium housing captive body screw Soft-grip handle **INCLUDES:** DONATION ■ 10 x Spare blades £ STORE COLLECTION ONLY

160 MM VDE COMBICUTTER1™

0043-6897

- · Pattress screw shear for damage free cutting of 3.5 mm pattress screws
- Drop forged, chrome vanadium steel for strength and durability
- Integral thumb guard
- 1.000V Rated
- VDE Safety certified





0305-8258

- · Wire stripping notches for damage free stripping of 1.5 and 2.5 mm² wire
- Pattress screw shear for damage free cutting of 3.5 mm pattress screws
- Drop forged chrome vanadium steel for strength and durability
- Integral thumb guard
- 1.000V Rated
- VDE Safety certified



160 MM VDE COMBICUTTER3™

- Wire stripping notches for damage free stripping of 1.5 and 2.5 mm² wire
- Wire bending anvil
- Pattress screw shear for damage free cutting of 3.5 mm pattress screws
- Drop-forged chrome vanadium steel for strength and durability
- Integral thumb guard
- 1,000V Rated
- VDE Safety certified

















ВАНСО

103 PCE ½" AND ¼" DRIVE SOCKET SET



2152-3273



- Ball point hex keys: 1.5, 2, 2.5, 3, 4, 5, 6, 8 and 10 mm
- Combination spanners: 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18 and 19 mm
- Hex bits: H3, H4, H5, H6, H7 and H8
- Phillips bits: PH1, PH2 and PH3
- Pozi bits: PZ1, PZ2 and PZ3
- Torx bits: T6. T8. T9. T10. T15. T20. T25. T30 and T40
- 5/16" Torx bits: T45, T50 and T55
- 1/4" Hex sockets: 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12 and 13 mm
- ¼" Hex deep sockets: 7, 8, 9, 10, 11 and 13 mm
- 1/4" Locking extension bar: 100 mm
- ¼" Universal joint
- 1/4" Spinner handle
- 1/4" Ratchet handle
- ¼" Ratchet spanner
- 1/4" Bit holder: 1/4"
- ¼" Hex x ¼" square adaptor
- Locking bit adaptor: Hex ¼" to hex ¼"
- ½" Hex sockets: 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 24, 27, 30, 32 and 34 mm
- ½" Hex deep sockets: 10, 13, 16, 17, 18 and 19 mm
- ½" Extension bars: 125 and 250 mm
- ½" Breaker bar: 250 mm
- ½" Universal joint
- ½" Spark plug sockets: 16 and 21 mm
- 1/2" Ratchet handle
- 1/2" Bit holder: 5/16"
- Storage case

18



000

54 PCE SCREWDRIVER BIT SET WITH **COLOUR-CODED TORX BITS**

2292-6391

- High-performance alloy steel
- Rubber-edged protective storage case

SET CONTENTS:

- Hex bits: H3, H4, H5, H6 and H8
- Phillips bits [25 mm]: 1 x PH1, 4 x PH2, 1 x PH3 and 2 x PH2G
- Phillips bits [125 mm]: PH1 and PH2
- Pozi bits [25 mm]: 1 x PZ1, 4 x PZ2 and 1 x PZ3
- Pozi bits [125 mm]: PZ1 and PZ2
- Robertson bits: R1 and R2 Slotted bits [25 mm]: SL4.5
- and SL5.5 mm
- Tamper torx bits [25 mm]: TX10, TX15, TX20, TX25 and TX30
- Torx bits [25 mm]: 2 x T10, 2 x T15, 4 x T20, 2 x T25, 1 x T27, 4 x T30 and 1 x T40
- Torx bits [150 mm]: T20, T25 and T30
- Magnetic bit holder
- Quick-release bit holder
- ¼" Hex to ¼" square socket adaptor
- Storage case

000

25 PCE METRIC SOCKET SET



2152-3186

 High-performance alloy steel with matt finish

SET CONTENTS:

- Hex bits: H5 and H6
- ¼" Hex sockets: 4, 4.5, 5.5, 6, 7, 8, 9, 10, 11, and 13 mm
- Phillips bits: PH2
- Torx bits: T10, T15, T20, T25, T30 and T40
- 1/4" Bit holder with locking spring
- ½" Compact ratchet handle: 60 Tooth / 6° action
- ½" Female square
- 100 mm Wobble extension bar
- Compact HDPE plastic case



0000000

CARBRIDE TIPPED HOLESAWS

- For cutting mild steel, steel plate, iron, aluminium, copper, brass, cast iron, stainless steel, fibreglass and plastics
- Tungsten carbide teeth deliver excellent wear and heat resistance
- Integral spring automatically ejects the slug for hassle-free drilling
- Use cutting oil to extend tooth life
- Use on rotation only: 300 1,000 rpm
- Max. Cutting depth: 5 mm

CODE	[Ø]	PRICE
0278-9437	20 mm	£22.95
0278-9443	25 mm	£24.95
0278-9446	32 mm	£31.95



FROM

Milwaukee

3 PCE SHEET STEEL HOLESAW KIT

TWISTER # ACCELER !"

armed

2042-4118

- Suitable for use with impact drivers on mild / stainless steel and aluminium
- 8% Cobalt for improved wear resistance
- Internal spring automatically ejects the metal disc for hassle-free drilling
- Replacement springs and drive adaptor / pilot drill available sold separately [2042-9944]
- Constant pitch: 8 tpi
- Cutting depth: 38 mm

KIT CONTENTS:

- Holesaws: 20, 25 and 32 mm
- Drive pilot Allen key: 25 mm
- Spring Storage case




15 PCE MASONRY FIXINGS INSTALLATION SET

2042-4070

- Featuring Twister impact rated screwdriver bits and drill bits
- ¼" Shank for rapid interchangeability

SET CONTENTS:

- Drill bits [150 mm]: 2 x 5.5 mm, 1 x 6, 7 and 8 mm
- Screwdriver bits [50 mm]: 1 x PH2, 4 x PZ2 and 1 x PZ3
- Screwdriver bits [75 mm]: 1 x PH2, 2 x PZ2 and 1 x PZ3
 Fabric tool roll





armeg

TWISTER 🎏

STREET,

19 PCE HSS-G THUNDERWEB™ **DRILL BIT SET**

1120-7041

- Incorporates a conical shaped web which gets thicker towards the back of the drill bit
- Flute form ejects hot chips rapidly and dissipates heat - increasing life time
- Flatter twist angle creates smaller chippings, ideal for drilling harder steel
- Split point: 135°

SET CONTENTS:


- 19 x Drill bits: 1 10 mm [includes half sizes]
- Storage case

49 PCE SHOCKWAVE™ DRILL **SCREWDRIVER BIT SET**

2610-6022

SET CONTENTS:

- Hex bits [25 mm]: 1 x H4 and H5
- Phillips bits [25 mm]: 2 x PH1, 2 x PH2 and 1 x PH3



- Pozi bits [25 mm]: 2 x PZ1, 4 x PZ2 and 1 x PZ3
- Pozi bits [50 mm]: 1 x PZ2
- Pozi bits [90 mm]: 1 x PZ2
- Slotted bits [25 mm]: 1 x SL4.5, SL5.5 and SL6.5
- Torx bits [25 mm]: 3 x TX10, 3 x TX15, 3 x TX20, 3 x TX25, 3 x TX30 and 1 x TX40
- Torx bits [50 mm]: 1 x TX10, TX15, TX20. TX25 and TX30
- Torx bits [90 mm]: 1 x TX20 and TX25
- Magnetic nut drivers: H3, H4, H5 and H6
- Magnetic bit holder: 60 mm















erennen.

3 PCE PACKOUT™ STORAGE SET

2369-6758

PACKOUT™ TOOLBOX

- Metal reinforced locking point
- Impact resistant
- Interior organiser trays

PACKOUT™ LARGE TOOLBOX

- Metal reinforced top handle for easier carrying
- Metal reinforced locking point
- Impact resistant

PACKOUT™ ROLLING TROLLEY TOOLBOX

- Max. Weight capacity: 113 kg
- 228 mm[Ø] All-terrain wheels
- Industrial grade extension handle
- Metal reinforced locking point

- IP65
- Dimensions: 560 mm[L] x 410 mm[W] x 170 mm[D]
- Interior organiser trays
- IP65
- Dimensions: 560 mm[L] x 410 mm[W] x 290 mm[D]

Interior organiser tray

- IP65
- Dimensions: 560 mm[L] x 410 mm[W] x 480 mm[D]





PACKOUT™ TOOL BOXES

- · Locking bar prevents drawers opening during transport
- Integrated quick adjust drawer dividers
- IP65
- Dimensions: 414 mm[L] x 563 mm[W] x 363 mm[D]

DESCRIPTION 2664-5290 2 Drawer 2664-5293 3 Drawer

PRICE £154.95 £164.95







- plywood top provides smooth work surface
- Compatible with the PACKOUT™ stacking system
- Dimensions: 650 mm[L] x 380 mm[W] x 60 mm[D]



M18 PACKOUT™ DAB RADIO AND CHARGER

2630-0467

20

- 360° Sound with moulded 10 speaker system for durability
- Compatible with the PACKOUT™ stacking system
- Charges all M18[™] batteries and USB devices
- Connectivity with Bluetooth[®] Aux and AM / FM





M18 PACKOUT™ **AREA LIGHT AND CHARGER**

2642-0269

- 3 Individual TRUEVIEW™ heads for multidirectional lighting with 9 light output modes
- · Compatible with the PACKOUT™ stacking system
- Charges all M18[™] batteries and USB devices
- Lumen output: 3,000 lm
- Runtime: 4 31 hrs.



M18 FUEL™ PACKOUT™ WET / DRY VACUUM

2642-0272

- POWERSTATE™ brushless motor for greater suction and airflow
- On-board accessory storage for easy transportation
- Compatible with the PACKOUT™ stacking system
- Max. Capacity: 11 Ltrs
- Max. Airflow: 1,416 Ltr / min

INCLUDES:

- 1.8 m Flexible hose
- Crevice tool
- Utility nozzle
- HEPA Filter







11 PCE VDE PACKOUT™ SET

2664-5296

- Compatible with the PACKOUT™ stacking system
- 3 Sided design for non-slip and maximum power transfer
- 1,000V Rated
- VDE Safety certified

SET CONTENTS:

- Philips: PH1 and PH2
- Pozi: PZ1 and PZ2
- Slotted: SL2.5. SL3 and SL4
- Voltage tester
- Diagonal cutter 160 mm
- Long nose plier 205 mm
- Combi plier 180 mm
- PACKOUT™ Slim Organiser







PACKOUT™ TECH BAG

2607-0262

- · Compatible with the PACKOUT™ stacking system • 1680D Ballistic weave
- for durability
- Hardshell protected instrument pocket
- Impact resistant polymer base protects contents from water and dirt
- No. of pockets: 58
- Dimensions: 430 mm[L] x 270 mm[W] x 450 mm[D]



PACKOUT™ **JOBSITE COOLER**

2566-1248

- Compatible with the PACKOUT™ stacking system
- Stavs cool for up to 24 hours
- Capacity: 20 Ltr
- Food grade leakproof liner
- Impact resistant base
- Dimensions: 380 mm[L] x 240 mm[W] x 330 mm[D]






PACKOUT™ 50 CM TOTE

- · Compatible with the PACKOUT™ stacking system
- 1680 Ballistic weave construction
- Impact resistant molded base
- Dimensions: 500 mm[L] x 250 mm[W] x 320 mm[D]

















F4P

TEST EQUIPMENT **CASE PLUS**

2633-3908

- Bright red inner lining for easy tool visibility
- Adjustable padded compartments
- Lockable zip system for extra security
- No. of pockets: 27
- Dimensions: 360 mm[L] x 240 mm[H] x 220 mm[D]



HEAVY-DUTY PROFESSIONAL TOOL BAG

2580-0331

- Wide opening for easy access
- 1200D Ballistic weave adds durability
- High visibility reflective strips
- Hard base for extra wear resistance
- No. of pockets: 20
- Dimensions: 440 mm[L] x 310 mm[H] x 250 mm[D]



WALL PLUG TRADE TUBS



■ P72 Screwdriver hit

■ Masonry drill hit

CODE	TUB CONTENTS	PACK	PRICE
0771-9787	Red Plugs + 8 x 1½" PZ2 Screws	500	£8.95
0771-9790	Brown Plugs + 10 x 2" PZ2 Screws	400	£9.95

16 OZ FIBREGLASS **CLAW HAMMER**





Drop-forged steel head

Shock-absorbing fibreglass shaft with nylon surround



ينعطك

ENGEX

armes MAGNETIC **SCREWDRIVER BITS**

2576-1964

- Magnetic collar locks onto the fastener
- Bit holds the fastener firmly at any orientation Handy dispenser
- box can be stacked together for convenience
- Size: PZ2
- Length: 50 mm

Pack of 6



SHOCKWAVE™ TIC TAC BOX

ENGEX

Engineered for extreme durability

- Innovatively designed geometric shock absorption zone
- to extend life Size: PZ2

2632-6798

- Length: 25 mm
- Pack of 25







GRINDING DISC

2190-3643

- Suitable for stainless and acid-resistant steel, hardox, heat-resistant cast steel spring steel, mild and tool steel
- Extended life and moisture protection
- Diameter: 115 mm[Ø]
- Thickness: 1 mm
- Bore: 22.23 mm
- Max. Speed: 80 m/s





FIBREGLASS STEPLADDERS

- Suitable for professional trade use
- Independently tested to non-conductive 30,000V rating
- Strengthened and deepened non-slip feet
- Integral tool rack
- Static load rating: 150 kg [Max.]
- FN 131

- LIV 131				
CODE	NO. OF TREADS	OPEN HEIGHT	CLOSED HEIGHT	PRIC
0413-1247	4	1.1 m	1.17 m	£59.9
0413-1253	5	1.3 m	1.47 m	£67.9
0413-1259	6	1.6 m	1.77 m	£73.9
0413-1262	8	2.2 m	2.37 m	£97.9
0554-0167	10	2.7 m	2.87 m	£127.9

ENGEX



FIBREGLASS HOP-UP PLATFORM

0697-5412

- Suitable for light trade use
- Easy set up, storage and transportation
- Double-locking hinges for added safety
- Surface: 600 mm x 600 mm
- Static load rating: 150 kg [Max.]
- Platform height: 480 mm
- No. of steps: 2



3-PART COMBINATION LADDER

0691-6276

- Extra wide stability bar
- Anti-slip feet
- 'A' frame height: 1.59 - 2.39 m
- 'A' frame width: 1.06 m
- Static load rating: 150 kg [Max.]
- No. of treads: 18
- Open height: 3.37 m
- Closed height: 1.7 m
- EN 131





EX

LADDER SAFETY TAG KIT

2150-1061

- Helps workers to identify if ladders are safe
- Can be used as part of a daily inspection and monitoring procedure to record and manage ladder inspections

KIT CONTENTS:

- Asset tag holder
- 2 x Inserts
- Permanent marker pen



ENGEX

SCAFFOLD SAFETY TAG KIT

2150-1094

- Helps workers to identify if scaffold is safe
- Can be used as part of a daily inspection and monitoring procedure to record and manage scaffold inspections

KIT CONTENTS:

- Claw tag holder
- 2 x Inserts
- Permanent marker pen



23













16A FLOOR STANDING CABLE REEL 110V

0834-5095

- Trade and industrial power distribution for 110V appliances
- Impact-resistant drum and toughened steel frame
- Recessed no shear sockets, neon power indicator and thermal cut out
- IP44
- BS EN 61242:1998

INCLUDES:

- 110V 16A 2P+E Plug
- 2 x 110V 16A 2P+F Sockets

- 2 X 110 V 10	UA ZFTL SUCKEIS			100-100	THE REAL PROPERTY OF THE PARTY
CODE	DESCRIPTION	CABLE LENGTH	PRICE	300	110
0834-5095	Light Duty Reel	25 m	£28.95		-
1492-7008	Heavy Duty Reel	50 m	£39.95	1000	300000
				A DESCRIPTION OF THE PARTY.	

AMAZING DEALS & EXCLUSIVE SPECIAL OFFERS

COTTON TWILL DUST SHEET

2081-1067

- 100% Cotton twill dust sheet
- Absorbent ideal for painters and decorators
- Washable
- Size: 3.6 m x 2.7 m



DOUBLE STRENGTH **RUBBLE SACKS**

2081-1088

- Double strength, heavy-duty rubble sacks
- Suitable for rubble, bricks. plaster, sand and gravel
- Size: 800 mm x 525 mm
- Pack of 6

bond it



ENGEX

SELF-FUSING RESCUE TAPE

- Resists fuels, oil, acids, solvents. salt water, road salt and UV
- Pressure resistant: Up to 8 bar
- Can be applied underwater
- Operating temperature: -50 to 260°C

CODE	COLOUR
1399-7410	Black
1399-7413	Blue
1399-7416	Clear
1399-7425	Red
1399-7428	White
1399-7431	Yellow

Insulation rating: 8,000V





INKZALL™ MARKER

1917-9733

- Suitable for writing on dusty, wet or oily surfaces
- Clog resistant



CABLE SPOOLER

0585-4966

- · Lightweight, cable carrier and stand
- Complete with five cable clips and rubber stoppers
- Folds flat for convenient storage
- Holds multiple reels
- Max. Carrying capacity: 45 kg





- 20. 25 and 32 mm mild steel conduit
- Portable and easy to set up

INCLUDES:

- Standard handle
- Arm extension tube
- Conduit vice
- Formers: 20. 25 and 32 mm



UPER

QUIKREEL **CABLE DISPENSER**

2560-9543

- Spinning top allows the user to easily load and draw cable from the reel
- Turns into a cable repair tool by removing the bottom stop and placing on cable stand
- Can be used with most popular cable reels
- Lightweight sturdy and compact



FOLDABLE **SACK TRUCK**

- Foldable sack truck for easy storage
- Folded size: 29¾"[H] x 15"[W] x 2¼"[D]
- Open size: 39%"[H] x 151/4"[W] x 13%"[D]
- Nose plate size: 15"[W] x 11"[D]
- 5" Solid rubber wheels
- Capacity: 150 lbs
- Guarantee: 1 Year













LED FLOODLIGHTS

- 100% and 50% Switchable output via On / Off button
- Run time: 3 hrs at 100% and 6 hrs at 50%
- Beam angle: 120°
- Colour temperature: Daylight 6000K

■ IP65

Guarantee: 2 Years

CODE	WATTAGE	LUMENS	PRICE
2467-2574	10W	600 lm	£21.95
2467-2577	20W	1300 lm	£32.95

Lamp life: 30.000 hrs

TUNILITE

- 5V USB Charging cable and charger
- Rechargeable lithium battery





TAMCO

TI UNILITE

HIGH CRI LED INSPECTION LIGHT

2583-5395

- Durable aluminium and polycarbonate casing
- Selectable colour temperature: Warm white 2700K, cool white 4500K and daylight 6500K
- 5W UV Light
- Retractable 360° rotating hanging hook
- Run time: 3 hrs [24 hrs low power]
- Lumen output: 1,250 lm beam [250 lm top torch]
- Beam distance: 58 m
- IP65: Water resistant
- Guarantee: 1 Year

INCLUDES:

- Magnetic charging dock
- Magnetic back and base
- 1 m USB Charging cable
- Rechargeable battery: Li-lon [5,000 mAh]





UNILITE

LED LANTERN

2641-9495

- Polycarbonate, ABS and aluminium construction
- Threaded hole in the base for attaching to tripods
- Run time: 6.5 hrs [28 hrs low power]
- Lumens: 1,000 lm Spot beam
- Lumens: 750 lm Floodlight base Guarantee: 1 Year

DONATION

Beam distance: 532 m

INCLUDES:

26

- Shoulder carry strap
- USB Charging cable
- Rechargeable battery: Li-lon [8,000 mAh]



IPX6: Water resistant

LED INSPECTION LAMP AND TORCH

2583-5389

- Durable aluminium and polycarbonate casing
- Run time: 3 12 hrs
- Lumen output: 625 lm [250 lm top torch]
- Beam distance: 46 m
- IP65: Water resistant
- Guarantee: 1 Year

INCLUDES:

- Magnetic back and base
- Handy pocket clip
- 1 m USB Charging cable
- Rechargeable battery: Li-lon [2,500 mAh]



TUNILITE

HELMET-MOUNTABLE **LED HEAD TORCH**

2429-7766

- Powerful Cree® LED
- · Easily attached to an industrial or sports helmet
- Rubberised non-slip headband
- Settings: High, medium and low with red on and red flash
- Run time: 6.5 hrs
- Lumens: 275 lm
- Beam distance: 95 m
- IPX6: Water resistant



INCLUDES:

- 3M[™] VHB[™] Adhesive helmet mount
- USB Charging cable
- Rechargeable battery: Li-polymer [1,800mAh]



POLO SHIRTS

- Slim fit
- 100% Polyester fabric
- Lightweight and quick drying
- Mesh panels provide improved breathability
- Raglan sleeve design for comfort and freedom of movement
- Zipped chest pocket and reflective detailing







Weils

TRADE FLEX SCRUIS HARD WEAR HOLSTER SHORTS



- 65% Polyester, 35% cotton ripstop
- Lightweight and durable
- Holster, cargo and mobile phone pockets
- Tool loops and D-ring for tool and accessory storage

SIZE
W30"
W32"
W34"
W36"
W38"
W40"







SPRAY ON ACCIDENT PLASTER

HEAVY-DUTY BIG WIPES

Dual-sided – scrub face

adhesives, epoxy, PU

foam, oil, grease and

■ Biodegradable formula

Antibacterial action

and smooth fabric

Removes paint,

2328-8851

1462-6369

more

■ Pack of 80

- Santises infected area providing a waterproof barrier against ingress of airborne and waterborne infections
- Protects against Weil's disease








BIG WIPES

ELECTROFLEX 5 FTR GLOVES



• HDPu coating for maximum abrasion resistance.

- Anti-bactrial treatment for hand hygiene
- Excellent dexterity and grip for safe use within high risk handling applications
- Cut resistance: Level 5
- EN 388: 2016 4X43D

CODE	SIZE
2083-0099	8
2083-0102	9
2083-0105	10



X-MIST SANITISER SPRAY 250ML

- Eradicates stubborn odours
- Leaves a clean fresh smell
- Remains active for up to 7 days after use
- Kills 99.999% of bacteria
- Coverage: 5 m x 5 m x 5 m

























IN-STORE

Open 6 days Monday-Friday 7:30am - 5:30pm Saturday 8:30am - 12:00pm



ONLINE

Choose from over 35,000 products in stock at cef.co.uk



CATALOGUE

Find your 8 digit order code - order in-store, online via the app or over the phone



CALL US

We have 390 stores nationwide so there's always a store near you

Whether online or in-store you can



CASH



CARD In-store and online



PAYPAL



BANK TRANSFER

MACMILLAN



Open a trade account today [in-store or online] and benefit from:

- Credit facilities (subject to credit checks)
 Online account management
- Monthly statements
- VAT approved itemised invoices
- View previous orders

FOR EVERY PRODUCT WITH AN 🙌 NEXT TO IT, WE* WILL DONATE THE AMOUNT STATED TO THE PRODUCT IN GREEN (PLUS VAT) TO MACMILLAN CANCER SUPPORT

*CITY ELECTRICAL FACTORS LTD **A REGISTERED CHARITY IN ENGLAND AND WALES (261017) SCOTLAND (SC039907) & IN THE ISLE OF MAN (604), ADDRESS 89 ALBERT EMBANKMENT LONDON SE1 7UQ. PAID TO MACMILLAN CANCER SUPPORT TRADING LIMITED, A WHOLLY OWNED SUBSIDIARY OF MACMILLAN CANCER SUPPORT TO WHICH IT GIVES ALL OF ITS PROFITS.







IN-STORE | CEF.CO.UK | TRADE CATALOGUE | APP