

FIRESTAR PRO LED

Recessed fire-rated, LED dimmable downlight with remote driver



Features:

- 9W Steel body Fire rated LED downlight
- Cast aluminium trim, available in 3 colour finishes (must be specified when ordering)
- Chip-on-board LED source replicates Halogen appearance
- Document P approved

Construction:

- Pressed steel can with fire rated protection
- Remote plug-in driver
- Cast aluminium trim

Options:

- /W White
- /SN Satin nickel
- /PC Polished chrome

FIRESTAR PRO LED

Recessed fire-rated, LED dimmable downlight with remote driver

Order Codes

All dimensions are in millimetres

Order Code	Lamp Value	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
TLED-888/WW	9W LED Module	525	9	64	0.39
TLED-888/NW	9W LED Module	525	9	64	0.39

Dimensions

All dimensions are in millimetres

Order Code	Height	Diameter	C	Cut Out
TLED-888/WW	90	90	102	71
TLED-888/NW	90	90	102	71

Installation Instructions:

Recessed into plasterboard or exposed grid ceiling via spring clips

Notes:

Add suffix to order code when choosing bezel colour option,
3 hour remote maintained emergency kit available

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact TamLite Lighting.



Tamlite Display.
T: 01527 528 556
F: 01527 526 671
E: starlite@tamlite.co.uk

Tamlite Technical.
T: 01952 292 441
F: 01952 292 155
E: technical@tamlite.co.uk

