

FRD MINI CC

FRD MINI CC



Features:

- Compact fire rated downlight with AC on board driver technology
- CCTK adjustable via simple 3-way selector switch
- Dimmable as standard
- Loop in/out mains connections with easy-fit connector
- White, satin nickel or polished chrome available
- Steel body providing a high level of fire protection in accordance with Building Regulations Part B
- 30, 60 & 90 minute fire rating with solid timber joists
- 30 minute fire rating with Staircraft I-Joist
- 30,000 hours lifetime

Construction:

- Convert to larger sized cut outs with the CONVERSION PLATES
- Up to 100 lumens per watt efficacy



FRD MINI CC

FRD MINI CC

Order Codes

All dimensions are in millimetres

Order Code	Description	Nominal Size	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCFRA5CTW	FRD 5W recessed fire rated downlight 60		400-500	5	100	0.15
XCFRA5CTSN	FRD 5W recessed fire rated downlight 60		400-500	5	100	0.15
XCFRA5CTPC	FRD 5W recessed fire rated downlight 60		400-500	5	100	0.15

Dimensions

All dimensions are in millimetres

Order Code	Diameter	C
XCFRA5CTW	80	57
XCFRA5CTSN	80	57
XCFRA5CTPC	80	57

