

# DOWNLIGHT BL

Downlight BL



## Features:

Backlit recessed downlight for corridors, reception areas, indoor circulation spaces, retail, toilets and shower rooms

More consistent and uniform appearance than traditional edge-lit downlights

Integrated driver

Available in 2 outputs

Plastic housing and reflector

Loop in/out 2-pole terminal

IP54 rated

30,000 hours lifetime (L70/B50)

## Construction:

Up to 100 lumens per watt efficacy



# DOWNLIGHT BL

Downlight BL

## Order Codes

All dimensions are in millimetres

Order Code	Description	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCBDL10NW	10W Recessed backlit downlight - 4000	850	10	85	0.15
XCBDL10WW	10W Recessed backlit downlight - 3000	700	10	70	0.15
XCBDL20NW	20W Recessed backlit downlight - 4000	2000	20	100	0.53
XCBDL20WW	20W Recessed backlit downlight - 3000	1900	20	95	0.53

## Dimensions

All dimensions are in millimetres

Order Code	Height	Diameter	Cut Out
XCBDL10NW	82	115	95
XCBDL10WW	82	115	95
XCBDL20NW	130	240	205
XCBDL20WW	130	240	205

