

# MINIFLOOD

LED Miniflood



## Features:

Slimline LED Miniflood

Low energy and maintenance free solution

Supplied with stirrup and 1.0m of flex

Suitable for replacement of halogen floodlights

Supplied in warm white (3000K) or daylight white (6000k)

Up to 75 lumens per watt efficacy

Available in 3 body sizes in black or white versions

20,000 hours lifetime (L70/B50)

## Construction:

Toughened glass cover

Die-cast aluminium body



# MINIFLOOD

LED Miniflood

## Order Codes

All dimensions are in millimetres

Order Code	Description	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCMF10BDL	10W LED Miniflood - 6000K - Black	600	10	60	0.32
XCMF10BWW	10W LED Miniflood - 3000K - Black	500	10	50	0.32
XCMF10WDL	10W LED Miniflood - 6000K - White	600	10	60	0.32
XCMF10WWW	10W LED Miniflood - 3000K - White	500	10	50	0.32
XCMF20BDL	20W LED Miniflood - 6000K - Black	1500	20	75	0.50
XCMF20WWW	20W LED Miniflood - 3000K - White	1400	20	70	0.50
XCMF20WDL	20W LED Miniflood - 6000K - White	1500	20	75	0.50
XCMF20BWW	20W LED Miniflood - 3000K - Black	1400	20	70	0.50
XCMF30BDL	30W LED Miniflood - 6000K - Black	2000	30	67	0.63
XCMF30WWW	30W LED Miniflood - 3000K - White	1800	30	60	0.63
XCMF30BWW	30W LED Miniflood - 3000K - Black	1800	30	60	0.63
XCMF30WDL	30W LED Miniflood - 6000K - White	2000	30	67	0.63

## Dimensions

All dimensions are in millimetres

Order Code	A	B	C
XCMF10BDL	130	90	35
XCMF10BWW	130	90	35
XCMF10WDL	130	90	35
XCMF10WWW	130	90	35
XCMF20BDL	180	126	35
XCMF20WWW	180	126	35
XCMF20WDL	180	126	35
XCMF20BWW	180	126	35
XCMF30BDL	210	147	35
XCMF30WWW	210	147	35
XCMF30BWW	210	147	35
XCMF30WDL	210	147	35

