

PANEL

Recessed LED panel



Features:

Ideal for retro-fit of existing T8 or T5 fixtures

High quality construction and optical performance

Available in 3 different sizes

Supplied in neutral white (4000K) or cool white (5000K) NB: (daylight (6500K) only available in 600 x 600)

SDCM <3 for consistent colour quality

2.5mm light guide

Remote emergency option also available

30,000 hours lifetime (L70/B50)

Construction:

Extruded aluminium frame

Opal PMMA diffuser



PANEL

Recessed LED panel

Order Codes

All dimensions are in millimetres

Order Code	Description	Nominal Size	Lumenss(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCRP6630CW	600mm x 600mm LED Recessed Panel - 5000K	600 x 600	3000	30	100	2.73
XCRP6630NW	600mm x 600mm LED Recessed Panel - 4000K	600 x 600	3000	30	100	2.73
XCRP12330CW	1200mm x 300mm LED Recessed Panel - 5000K	1200 x 300	3000	30	100	2.76
XCRP12330NW	1200mm x 300mm LED Recessed Panel - 4000K	1200 x 300	3000	30	100	2.76
XCRP12650CW	1200mm x 600mm LED Recessed Panel - 5000K	1200 x 600	5000	50	100	5.90
XCRP12650NW	1200mm x 600mm LED Recessed Panel - 4000K	1200 x 600	5000	50	100	5.90
XCRP6630DL	600mm x 600mm LED Recessed Panel - 6000K	600 x 600	3000	30	100	2.73

Dimensions

All dimensions are in millimetres

Order Code	A	B	C
XCRP6630CW	595	595	10
XCRP6630NW	595	595	10
XCRP12330CW	1200	300	10
XCRP12330NW	1200	300	10
XCRP12650CW	1200	600	10
XCRP12650NW	1200	600	10
XCRP6630DL	595	595	10

